

# **Application:**

Industries, Factory, Goods yard, Commercial premises, Apartments, Access shopping malls, Hospitals, Stadiums, Business centers, and so on.

# **Automatic Retractable gates**



### **Specification:**

Material: 304 Stainless Steel

Major material: 50\*50\*0.7mm

• Auxiliary Material: 46\*36\*0.6mm

Auxiliary Material: 38\*25\*0.6mm


Wheel: casting aluminum 3.3 cross net tubes

 Heavy duty Motor+ LED+ Remote (20mtr /min)

AC Input Voltage	220V/50HZ
AC Input Power	220V/5HZ / 350Watts~1000 Watts
Speed of Open	Suitable for Max 20mt/Minute
Motor	Intelligent Gear Motor
Gate Size	Height 1.2- 2 Mt / Width 3- 30Mt
Track Type	Single/Double/Trackless
Manual Operation	By Clutch Key on Power Fail
Standard Accessories	Electric Switch/Remote Controller/Clutch Keys for Manual Operation with User Manual
Gate Material	Stainless Steel / Aluminum
Controller	Microprocessor Based controller


### **Stainless Steel Materials**





## **Aluminum Retractable Gate**





Material	201 SS / 304SS /AL
Height (MM)	1200 - 1800
Width(MM)	660
Weight of gate	Max 1000 Kg
Wheel Base	600-610mm
(center -center)	_
Working Temp	-35+75°C
Moving Speed	17-19m/min
(mtrs/min)	·
Remote Control	≤50m
with range	
Main Parts Material	50*50*0.7mm
Vice Parts Material	46*36*0.6mm
Power Consumption	420W
Motor Tracking Options	Single track / Double track /Trackless
Colors	Steel color
LED Display(Optional Accessories)	1 set
Alarm Light(Optional Accessories)	1 set
Anti-Climb alarm system	1set
Motor Overheating Protection	yes
Speed Clutch	1рс
Infrared Anti-Collision Device	1рс
Anti-Climb Alarm (Optional)	1 set

### **ACCESSORIES**

Motor



**Control Panel** 



Rolling Display Screen



Magic Eye Alarm



Anti crash Device



# Robot Navigation Alarm Light Wireless Remote Control Wheel